

500HF - Cutter-head Attachment for "High-Flow" Machines

The 500HF is the standard Cutter-head shipped with our medium-duty mulching machines and is also available for High-flow Skid Steers and Compact Track Loaders with a minimum hydraulic flow of 30 gpm.

The 500HF attaches quickly and easily on any high flow Skid Steer or Compact Track Loader without the need for special hoses or couplings.

With the 500HF you can...

- Cut a tree and completely mulch it into fine wood chips
- Grind dozens of stumps to the ground in less than half-a-day
- Perform rapid, high-quality, low-cost right-of-way maintenance
- Cost effectively cut miles of survey lines or fence lines
- Clear acres of small trees and underbrush in a single day
- Outperform any high-flow Skid Steer or Compact Track Loader Cutter-head attachment on the market

SPECIFICATIONS:*

Cutting Width	64"	163cm
Overall Width	77"	196cm
Overall Height	68"	173cm
Weight	2400 LBS.	1089 kg

CUTTER-HEAD

Number of Teeth	23
Recommended RPM	2350
Tractor HP	80-140 HP
Max. Hyd. Flow	50 gpm
Min. Hyd. Flow	30 gpm
Max. Case Drain Pressure (Continuous)	43 psi
Min. Case Drain Pressure (Cold Start)	73 psi

* Specifications are based on published information at time of publication and are subject to change without notice.



Gyro-Trac Corporation
10 Flying Cloud Drive
Summerville, SC 29483



visit: www.gyrotrac.com
for demo videos
email: sales@gyrotrac.com
866-800-3900